




COAXIAL CABLES




10-32 MALE PLUG	TO	10-32 MALE PLUG
RG178, RG196A/U		
P5026-3-178	P5026-6-178	P5026-12-178
P5026-3-196	P5026-6-196	P5026-12-196



10-32 MALE PLUG	TO	10-32 MALE PLUG
RG174, RG316, RG188		
P5048-3-174	P5048-6-174	P5048-12-174
P5048-3-316	P5048-6-316	P5048-12-316
P5048-3-188	P5048-6-188	P5048-12-188



10-32 MALE PLUG	TO	10-32 90 DEG. MALE PLUG
RG178, RG196A/U		
P5043-3-178	P5043-6-178	P5043-12-178
P5043-3-196	P5043-6-196	P5043-12-196



10-32 MALE PLUG	TO	10-32 90 DEG MALE PLUG
RG174, RG316, RG188		
P5100-3-174	P5100-6-174	P5100-12-174
P5100-3-316	P5100-6-316	P5100-12-316
P5100-3-188	P5100-6-188	P5100-12-188



10-32 90 DEG MALE PLUG	TO	10-32 90 DEG. MALE PLUG
RG178, RG196A/U		
P5101-3-178	P5101-6-178	P5101-12-178
P5101-3-196	P5101-6-196	P5101-12-196



10-32 90 DEG MALE PLUG	TO	10-32 90 DEG. MALE PLUG
RG174, RG316, RG188		
P5102-3-174	P5102-6-174	P5102-12-174
P5102-3-316	P5102-6-316	P5102-12-316
P5102-3-188	P5102-6-188	P5102-12-188



STANDARD LENGTHS SHOWN - 3 FOOT, 6 FOOT, 12 FOOT - CONTACT FACTORY FOR NON-STANDARD LENGTHS
 ALL STANDARD CABLES ARE NORMALLY STOCK OR "STOCK TO BUILD"
 10-32 AND 5-44 CONNECTORS ARE INTERMATEABLE AND INTERCHANGEABLE WITH TE / MALCO-MICRODOT CONNECTORS
 CONTACT FACTORY FOR ANY CABLE / CONNECTOR COMBINATIONS NOT SHOWN

COAXIAL CABLES



10-32 FEMALE RECEPTACLE	TO	10-32 MALE PLUG
	RG178, RG196A/U	
P5103-3-178	P5103-6-178	P5103-12-178
P5103-3-196	P5103-6-196	P5103-12-196




10-32 FEMALE RECEPTACLE	TO	10-32 MALE PLUG
	RG174, RG316, RG188	
P5104-3-174	P5104-6-174	P5104-12-174
P5104-3-316	P5104-6-316	P5104-12-316
P5104-3-188	P5104-6-188	P5104-12-188




10-32 FEMALE BULKHEAD RECEPTACLE	TO	10-32 MALE PLUG
	RG178, RG196A/U	
P5105-3-178	P5105-6-178	P5105-12-178
P5105-3-196	P5105-6-196	P5105-12-196



10-32 FEMALE BULKHEAD RECEPTACLE	TO	10-32 MALE PLUG
	RG174, RG316, RG188	
P5106-3-174	P5106-6-174	P5106-12-174
P5106-3-316	P5106-6-316	P5106-12-316
P5106-3-188	P5106-6-188	P5106-12-188



10-32 MALE PLUG	TO	BNC MALE PLUG
	RG178, RG196A/U	
P5023-3-178	P5023-6-178	P5023-12-178
P5023-3-196	P5023-6-196	P5023-12-196



10-32 MALE PLUG	TO	BNC MALE PLUG
	RG174, RG316, RG188	
P5046-3-174	P5046-6-174	P5046-12-174
P5046-3-316	P5046-6-316	P5046-12-316
P5046-3-188	P5046-6-188	P5046-12-188



STANDARD LENGTHS SHOWN - 3 FOOT, 6 FOOT, 12 FOOT - CONTACT FACTORY FOR NON-STANDARD LENGTHS
 ALL STANDARD CABLES ARE NORMALLY STOCK OR "STOCK TO BUILD"
 10-32 AND 5-44 CONNECTORS ARE INTERMATEABLE AND INTERCHANGEABLE WITH TE / MALCO-MICRODOT CONNECTORS
 CONTACT FACTORY FOR ANY CABLE / CONNECTOR COMBINATIONS NOT SHOWN

COAXIAL CABLES




5-44 MALE PLUG TO 10-32 MALE PLUG
RG178, RG196A/U

P5001-3-178	P5001-6-178	P5001-12-178
P5001-3-196	P5001-6-196	P5001-12-196





5-44 MALE PLUG TO BNC MALE PLUG
RG178, RG196A/U

P5040-3-178	P5040-6-178	P5040-12-178
P5040-3-196	P5040-6-196	P5040-12-196




10-32 MALE PLUG TO PIGTAIL
RG178, RG196A/U

P5041-3-178	P5041-6-178	P5041-12-178
P5041-3-196	P5041-6-196	P5041-12-196




10-32 MALE PLUG TO PIGTAIL
RG174, RG316, RG188

P5107-3-174	P5107-6-174	P5107-12-174
P5107-3-316	P5107-6-316	P5107-12-316
P5107-3-188	P5107-6-188	P5107-12-188




5-44 MALE PLUG TO PIGTAIL
RG178, RG196A/U

P5116-3-178	P5116-6-178	P5116-12-178
P5116-3-196	P5116-6-196	P5116-12-196




10-32 90 DEG MALE PLUG TO PIGTAIL
RG174, RG316, RG188

P5117-3-174	P5117-6-174	P5117-12-174
P5117-3-316	P5117-6-316	P5117-12-316
P5117-3-188	P5117-6-188	P5117-12-188




STANDARD LENGTHS SHOWN - 3 FOOT, 6 FOOT, 12 FOOT - CONTACT FACTORY FOR NON-STANDARD LENGTHS
ALL STANDARD CABLES ARE NORMALLY STOCK OR "STOCK TO BUILD"
10-32 AND 5-44 CONNECTORS ARE INTERMATEABLE AND INTERCHANGEABLE WITH TE / MALCO-MICRODOT CONNECTORS
CONTACT FACTORY FOR ANY CABLE / CONNECTOR COMBINATIONS NOT SHOWN


COAXIAL CABLES - LOW NOISE




10-32 MALE PLUG TO 10-32 MALE PLUG
RG196A/U LOW NOISE
P5049-3-196LN P5049-6-196LN P5049-12-196LN




10-32 MALE PLUG TO 10-32 90 DEG MALE PLUG
RG196A/U LOW NOISE
P5108-3-196LN P5108-6-196LN P5108-12-196LN



10-32 MALE PLUG TO BNC MALE PLUG
RG196A/U LOW NOISE
P5034-3-196LN P5034-6-196LN P5034-12-196LN



10-32 MALE PLUG TO PIGTAIL
RG196A/U LOW NOISE
P5027-3-196LN P5027-6-196LN P5027-12-196LN




5-44 MALE PLUG TO 10-32 MALE PLUG
RG196A/U LOW NOISE
P5028-3-196LN P5028-6-196LN P5028-12-196LN



5-44 MALE PLUG TO BNC MALE PLUG
RG196A/U LOW NOISE
P5030-3-196LN P5030-6-196LN P5030-12-196LN




5-44 MALE PLUG TO PIGTAIL
RG196A/U LOW NOISE
P5031-3-196LN P5031-6-196LN P5031-12-196LN




STANDARD LENGTHS SHOWN - 3 FOOT, 6 FOOT, 12 FOOT - CONTACT FACTORY FOR NON-STANDARD LENGTHS
ALL STANDARD CABLES ARE NORMALLY STOCK OR "STOCK TO BUILD"
10-32 AND 5-44 CONNECTORS ARE INTERMATEABLE AND INTERCHANGEABLE WITH TE / MALCO-MICRODOT CONNECTORS
CONTACT FACTORY FOR ANY CABLE / CONNECTOR COMBINATIONS NOT SHOWN


COAXIAL CABLES - LOW NOISE




10-32 MALE PLUG TO 10-32 MALE PLUG
RG174 LOW NOISE
P5109-3-174LN P5109-6-174LN P5109-12-174LN




10-32 MALE PLUG TO 10-32 90 DEG MALE PLUG
RG174 LOW NOISE
P5110-3-174LN P5110-6-174LN P5110-12-174LN




10-32 MALE PLUG TO BNC MALE PLUG
RG174 LOW NOISE
P5111-3-174LN P5111-6-174LN P5111-12-174LN




10-32 MALE PLUG TO PIGTAIL
RG174 LOW NOISE
P5112-3-174LN P5112-6-174LN P5112-12-174LN



10-32 MALE PLUG TO 10-32 MALE PLUG
RG188 LOW NOISE
P5113-3-188LN P5113-6-188LN P5113-12-188LN



10-32 MALE PLUG TO 10-32 90 DEG MALE PLUG
RG188 LOW NOISE
P5114-3-188LN P5114-6-188LN P5114-12-188LN



10-32 MALE PLUG TO BNC MALE PLUG
RG188 LOW NOISE
P5115-3-188LN P5115-6-188LN P5115-12-188LN



STANDARD LENGTHS SHOWN - 3 FOOT, 6 FOOT, 12 FOOT - CONTACT FACTORY FOR NON-STANDARD LENGTHS
ALL STANDARD CABLES ARE NORMALLY STOCK OR "STOCK TO BUILD"
10-32 AND 5-44 CONNECTORS ARE INTERMATEABLE AND INTERCHANGEABLE WITH TE / MALCO-MICRODOT CONNECTORS
CONTACT FACTORY FOR ANY CABLE / CONNECTOR COMBINATIONS NOT SHOWN

COAXIAL CABLES - Connector Specifications

MSW-CX10-32 COAXIAL CONNECTOR SPECIFICATIONS

MATERIALS		ELECTRICAL	ENVIRONMENTAL
SHELL:	Brass per ASTM-B-16	DIELECTRIC WITHSTANDING	TEMP RANGE: -62C to +200C
INSULATOR:	PTFE per ASTM-G-1710	VOLTAGE: 1000V RMS.	VIBRATION: Per MIL-STD-202, Method 204-B
PIN CONTACT :	Brass per ASTM-B-16	CONTACT RESISTANCE: 3 milliohms max DC	SHOCK: Per MIL-STD-202, Method 213-H
SOCKET CONTACT:	Beryllium Copper per ASTM-B-196	CURRENT CAPACITY: 3 amps, DC	THERMAL SHOCK: Per MIL-STD-202, Method 107-B
O-Ring, Boot:	Silicone per ZZ-R-765	INSULATION RESISTANCE: 5 X 10(3) Megohms min - 500V,DC	Moisture Resistance: Per MIL-STD-202 Method 106
PLATING		VSWR: Typical 50 Ohm , 1.2 max to 2 GHz	SALT SPRAY: Per MIL-STD-202, Method 101-B
CONTACT:	Gold per MIL-G-45204	MECHANICAL	
SHELL:	Gold per MIL-G-45204		
		CABLE RETENTION: 15 lbs min	
		RECOMMENDED	
		COUPLING TORQUE: 8 inch/lbs max	

MSW-CX544 COAXIAL CONNECTOR SPECIFICATIONS

MATERIALS		ELECTRICAL	ENVIRONMENTAL
SHELL:	Brass per ASTM-B-16	DIELECTRIC WITHSTANDING	TEMP RANGE: -62C to +200C
INSULATOR:	PTFE per ASTM-G-1710	VOLTAGE: 450 V RMS.	VIBRATION: Per MIL-STD-202, Method 204-B
PIN CONTACT :	Brass per ASTM-B-16	CONTACT RESISTANCE: 8 milliohms max DC	SHOCK: Per MIL-STD-202, Method 213-H
SOCKET CONTACT:	Beryllium Copper per ASTM-B-196	CURRENT CAPACITY: 3 amps, DC	THERMAL SHOCK: Per MIL-STD-202, Method 107-B
O-Ring, Boot:	Silicone per ZZ-R-765	INSULATION RESISTANCE: 10(4) Megohms min - 500V,DC	MOISTURE RESISTANCE: Per MIL-STD-202 Method 106
PLATING		VSWR: Typical 50 Ohm , 1.2 max to 2 GHz	SALT SPRAY: Per MIL-STD-202, Method 101-B
CONTACT:	Gold per MIL-G-45204	MECHANICAL	
SHELL:	Gold per MIL-G-45204		
		CABLE RETENTION: 10 lbs min	
		RECOMMENDED	
		COUPLING TORQUE: 24 inch/oz max	

MSW-BNC COAXIAL CONNECTOR SPECIFICATIONS

MATERIALS		ELECTRICAL	ENVIRONMENTAL
SHELL:	Brass per ASTM-B-16	DIELECTRIC WITHSTANDING	TEMP RANGE: -62C to +165C
INSULATOR:	PTFE per ASTM-G-1710	VOLTAGE: 1500V RMS.	VIBRATION: Per MIL-STD-202, Method 204-B
PIN CONTACT :	Brass per ASTM-B-16	CONTACT RESISTANCE: 1.53 milliohms max DC	SHOCK: Per MIL-STD-202, Method 213-H
SOCKET CONTACT:	Beryllium Copper per ASTM-B-196	CURRENT CAPACITY: 3 amps, DC	THERMAL SHOCK: Per MIL-STD-202, Method 107-B
O-Ring, Boot:	Silicone per ZZ-R-765	INSULATION RESISTANCE: 5000 Megohms min - 500V,DC	MOISTURE RESISTANCE: Per MIL-STD-202 Method 106
PLATING		VSWR: Typical 50 Ohm , 1.3 max to 2 GHz	SALT SPRAY: Per MIL-STD-202, Method 101-B
CONTACT:	Gold per MIL-G-45204	MECHANICAL	
SHELL:	Electroless Nickel		
		CABLE RETENTION: 20 lbs min	
		RECOMMENDED	
		COUPLING TORQUE: 12 inch/lbs max	

MILSPECWEST - The Very Best in Micro Interconnect Products



AEROSPACE * MEDICAL * AUTOMOTIVE * INDUSTRIAL * MICRO-ELECTRONICS milspecwest.com
sales@milspecwest.com 888-428-2188

COAXIAL CABLES - CABLE TRIM SPEC IFICATION

BNC - PLUG, MALE


RG178, RG196A/U

ASSEMBLY INSTRUCTIONS




1

- 1-1 Place boot and ferrule onto the cable
- 1-2 Strip the cable as shown




2

- 2-1 Disperse Shielding layer of the cable.



3

- 3-1 Position the body onto the cable
- 3-2 Solder the contact
- 3-3 Push the ferrule onto the body.





4

- 4-1 Crimp ferrule with 2.54 mm Hex Crimp Die
- 4-2 Pull the boot over the ferrule

COAXIAL CABLES - CABLE TRIM SPEC IFICATION


BNC - PLUG, MALE RG174, RG319, RG188

ASSEMBLY INSTRUCTIONS




1

- 1-1 Place boot and ferrule onto the cable
- 1-2 Strip the cable as shown




2

- 2-1 Disperse Shielding layer of the cable.



3

- 3-1 Position the body onto the cable
- 3-2 Solder the contact
- 3-3 Push the ferrule onto the body.





4

- 4-1 Crimp ferrule with 4.52 mm Hex Crimp Die
- 4-2 Pull the boot over the ferrule

COAXIAL CABLES - CABLE TRIM SPEC IFICATION

MSW -CX1032 RG178, RG196A/U

ASSEMBLY INSTRUCTIONS




1

- 1-1 Place boot and ferrule onto the cable
- 1-2 Strip the cable as shown



2

- 2-1 Disperse Shielding layer of the cable.



3

- 3-1 Position the body onto the cable
- 3-2 Solder the contact
- 3-3 Push the ferrule onto the body.



4



- 4-1 Crimp ferrule with 2.54 mm Hex Crimp Die
- 4-2 Pull the boot over the ferrule

COAXIAL CABLES - CABLE TRIM SPEC IFICATION

MSW-CX1032


RG174, RG316, RG188

ASSEMBLY INSTRUCTIONS



1

- 1-1 Place boot and ferrule onto the cable
- 1-2 Strip the cable as shown



2

- 2-1 Solder the contact
- 2-2 Disperse Shielding layer of the cable.



3

- 3-1 Position the body onto the cable
- 3-2 Push the ferrule onto the body.



4

- 4-1 Crimp ferrule with 4.52 mm Hex Crimp Die
- 4-2 Pull the boot over the ferrule