




## M12 Female Field Wirable Assembly, Angled, Solder

- Connector series: M12
- Gender: Female
- Coding: A,B,C,D
- Locking type: Fix screw
- Mounting type: Right angled
- Part No.: MB12FA\*FF\*\*RA

\* refers to coding type

\*\* refers to pins number



### General information

Standard:	IEC 61076-2-101	Insulation resistance:	≥ 100MΩ
Ambient temperature:	-25°C ~ +90°C	Contact resistance :	≤ 5mΩ
Connector insert:	PA+GF	Shielding:	Unavailable
Connector contacts:	Brass with gold plated	Suitable cable Dia:	4~5.5mm
Connector nut/screw:	Brass with nickel plated	IP rating:	IP68 in locked condition
Connector body:	PA+GF	Assembly Instruction:	Refer to page 283
Seal / O-ring:	FKM	Mating endurance:	>500 cycles

### Electrical data & Mechanical data

Contacts	Available Coding				Contacts termination	Rated current	Voltage		Wire gauge / size		Cable jacket	Part No.
	A	B	C	D			A/C	D/C	AWG	mm <sup>2</sup>		
03 pins					Solder version	4A	250V	250V	22AWG	0.34	PUR/PVC or customized	MB12FAAFF03RA MB12FABFF03RA MB12FACFF03RA
04 pins					Solder version	4A	250V	250V	22AWG	0.34	PUR/PVC or customized	MB12FAAFF04RA MB12FABFF04RA MB12FACFF04RA MB12FADFF04RA
05 pins					Solder version	4A 2A (C-code)	60V	60V	22AWG 24AWG (C-code)	0.34 0.25 (C-code)	PUR/PVC or customized	MB12FAAFF05RA MB12FABFF05RA MB12FACFF05RA
06 pins					Solder version	2A	30V	30V	24AWG	0.25	PUR/PVC or customized	MB12FACFF06RA
08 pins					Solder version	2A	30V	30V	24AWG	0.25	PUR/PVC or customized	MB12FAAFF08RA

### Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm<sup>2</sup>.
- Please refer to Page 96 for products' part number encoding rule.