




## M12 Male Panel Mount, Crimp, Front fastened, S-coding

- Connector series: M12
- Gender: Male
- Coding: S
- Locking type: Fix screw
- Mounting type: Front fastened
- Part No.: MB12MCSFF\*\*ST-XXXX

\*\* refers to pins number

X refers to Chasis-side thread size

XXX refers to cable specification



### General information

Ambient temperature: -20°C ~ +80°C

Connector insert: PA

Connector contacts: Brass with gold plated

Connector screw/nut: Brass with nickel plated

Seal / O-ring: Epoxy resin / FKM

Insulation resistance:  $\geq 100M\Omega$

Contact resistance :  $\leq 5m\Omega$


Shielding: Unavailable

IP rating: IP68 in locked condition

Panel cut-out: Refer to page 287

Mating endurance: >500 cycles

### Electrical data & Mechanical data

Contacts	Contacts termination	Rated current	Rated voltage	Wire gauge / size		Wire insulation	Part No.
				AWG	mm <sup>2</sup>		
04 pins  (3 + PE)	Crimp version	12A(40°C)	630V	16AWG	1.5	PVC wire or customized	MB12MCSFF04ST- <u>X</u> 150

Note: X refers to Chasis-side thread size

### Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm<sup>2</sup>.
- Please refer to Page 96 for products' part number encoding rule.