

M12 Plastic I-Adapter, Male-Female


Connector series: M12Gender: Male&Female

• Coding: A,B,D

• Locking type: Plastic fix screw

Mounting type: I typePart No.: MIP-*XX

* refers to coding type XX refers to pins number





c**¶u**s (€ RoHS ∰

■ General information

Standard:	IEC 61076-2-101				
Ambient temperature:	-20℃~ + 80℃				
Connector insert:	TPU; PA				
Connector contacts:	Brass with gold plated				
Connector nut/screw:	PA+GF				
Connector overmold:	TPU				
Seal/O-ring:	FKM				

Insulation resistance:	≥100MΩ
Contact resistance :	≤5mΩ
Shielding:	Unavailable
IP rating:	IP68 in locked condition
Mating endurance:	>500 cycles

■ Electrical data & Mechanical data

Contosts	Available Coding			Rated	Voltage		Dort No.
Contacts	А	В	D	current	A/C	D/C	Part No.
03 pins	Male Female	Male Female		4A	250V	250V	MIP-A03 MIP-B03
04 pins	(4) (3) (3) (4) (2) (1) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4	4 * 3 (30 04) (30 01) Male Female	4 • • • • • • • • • • • • • • • • • • •	4A	250V	250V	MIP-A04 MIP-B04 MIP-D04
05 pins	(4) (8) (3) (4) (5) (4) (5) (7) (7) (7) (7) (7) (7) (7) (7) (7) (7	4 * 3 (30 04 05 1) Male Female		4A	60V	60V	MIP-A05 MIP-B05
08 pins	(60 5 04) (70 8 8 3) (10 5 06) (30 0 07) (20 8 01) Male Female			2A	30V	30V	MIP-A08