

## M12 Plastic L-Adapter, Male-Female


• Connector series: M12 • Gender: Male&Female

• Coding: A,B,D

• Locking type: Plastic fix screw

• Mounting type: L type • Part No.: MLP-\*XX

\* refers to coding type XX refers to pins number









## ■ General information

Standard:	IEC 61076-2-101				
Ambient temperature:	-20℃~ + 80℃				
Connector insert:	TPU; PA				
Connector contacts:	Brass with gold plated				
Connector nut/screw:	PA+GF				
Connector overmold:	TPU				
Seal/O-ring:	FKM				

Insulation resistance:	≥100MΩ
Contact resistance :	≤5mΩ
Contact resistance :	≥ 2111C ≥
Shielding:	Unavailable
IP rating:	IP68 in locked condition
ir rating.	IF 00 III locked condition
Mating endurance:	>500 cycles

## ■ Electrical data & Mechanical data

Contosts	Available Coding		Rated	Voltage		Dort No.	
Contacts	A	В	D	current	A/C	D/C	Part No.
03 pins	Male Female	Male Female		4A	250V	250V	MLP-A03 MLP-B03
04 pins	(4) (3) (3) (04) (2) (1) (1) (1) (1) (1) (1) (1) (1) (1) (1	4 * 3 (30 04 ) (30 01) Male Female	4 • • • • • • • • • • • • • • • • • • •	4A	250V	250V	MLP-A04 MLP-B04 MLP-D04
05 pins	(4) (8) (3) (4) (5) (4) (5) (7) (7) (7) (7) (7) (7) (7) (7) (7) (7	4 * 3 (30 04 05 1) Male Female		4A	60V	60V	MLP-A05 MLP-B05
08 pins	(60 5 04) (70 8 8 3) (10 5 06) (30 0 07) (20 8 01) Male Female			2A	30V	30V	MLP-A08