




M8 Male Molded Cable, Angled, Shielded

- Connector series: M8
- Gender: Male
- Coding: A,B
- Locking type: Fix screw
- Mounting type: Right angled
- Part No.: MA08MS*F**RAXXXXXX

* refers to coding type
** refers to pins number
X refers to cable specification



General information

Standard:	IEC 61076-2-104
Ambient temperature:	-40°C ~ +80°C (fixed installation) -20°C ~ +80°C (flexible installation)
Connector insert:	TPU
Connector contacts:	Brass with gold plated
Connector overmold:	TPU
Connector nut/screw:	Brass with nickel plated

Insulation resistance:	≥ 100MΩ
Contact resistance:	≤ 5mΩ
Shielding:	Available (not 360° shielded)
IP rating:	IP67 in locked condition
Mating endurance:	>500 cycles

Electrical data & Mechanical data

Contacts	Rated current	Voltage		Wire gauge / size		Cable jacket	Part No.
		A/C	D/C	AWG	mm ²		
03 pins (A-coding)	3A	50V	60V	24AWG	0.25	PVC	MA08MSAF03RAXXCB25
						PUR	MA08MSAF03RAXXRB25
04 pins (A-coding)	3A	50V	60V	24AWG	0.25	PVC	MA08MSAF04RAXXCB25
						PUR	MA08MSAF04RAXXRB25
05 pins (B-coding)	3A	30V	30V	24AWG	0.25	PVC	MA08MSBF05RAXXCB25
						PUR	MA08MSBF05RAXXRB25
06 pins (A-coding)	1.5A	30V	30V	26AWG	0.14	PVC	MA08MSAF06RAXXCB14
						PUR	MA08MSAF06RAXXRB14
08 pins (A-coding)	1.5A	30V	30V	26AWG	0.14	PVC	MA08MSAF08RAXXCB14
						PUR	MA08MSAF08RAXXRB14

Note: X refers to cable length

Remarks

- Please refer to Page 578 for the Conversion between American Wire Gauge AWG and Wire Cross-section mm².
- Please refer to Page 22 for products' part number encoding rule.