

PSG.0B.307.CLAD52Z PUSH-PULL PLUG, 7 PIN CONTACTS, SOLDER, 5.2 MM COLLET, STRAIN RELIEF NUT







KEY SPECIFICATIONS	
CONNECTOR SERIES	PSG
CONNECTOR SIZE	0B
CONNECTOR GENDER	MALE
CODING	G
LOCKING STYLE	SELF LOCKING
ATTACHMENT METHOD	SOLDER
IP RATING	IP 50
COLLET SIZE	5.2 MM
STANDARD MATE SERIES	FSG

GENERAL SPECIFICATIONS		
TEMPERATURE RANGE	-55 DEG C - +200 DEG C	
INSULATOR MATERIAL	PEEK	
SOLDER CONTACT MATERIAL	COPPER ALLOY, GOLD PLATED	
CONNECTOR BODY MATERIAL	BRASS, NICKEL PLATED	
COUPLING NUT, SCREW	BRASS, CHROME PLATED	
INSULATION RESISTANCE	EQUAL OR GREATER THAN 100 M-OHMS	

MILSPECWEST - The Very Best in Micro Interconnect Products AEROSPACE * MEDICAL * AUTOMOTIVE * INDUSTRIAL * MICRO-ELECTRONICS milspecwest.com sales@milspecwest.com 949-636-9677