
FSG.1B.314.CLL PUSH-PULL FXIED SOCKET RECEPTACLE 14 CONTACTS, SOLDER





CONTACT INFO		DIA
MALE	FEMALE	mm
		0.5

KEY SPECIFICATIONS		
CONNECTOR SERIES	FSG	
CONNECTOR SIZE	1B	
CONNECTOR GENDER	FEMALE	
CODING	G	
LOCKING STYLE	SELF LOCKING	
ATTACHMENT METHOD	SOLDER	
IP RATING	IP 50	
STANDARD MATE SERIES	PSG	

GENERAL SPECIFICATIONS		
TEMPERATURE RANGE	-55 DEG C - +200 DEG C	
INSULATOR MATERIAL	PEEK	
SOLDER CONTACT MATERIAL	COPPER ALLOY, GOLD PLATED	
CONNECTOR BODY MATERIAL	BRASS, NICKEL PLATED	
COUPLING NUT, SCREW	BRASS, CHROME PLATED	
INSULATION RESISTANCE	EQUAL OR GREATER THAN 100 M-OHMS	

MILSPECWEST- The Very Best in Micro Interconnect ProductsAEROSPACE* MEDICAL* AUTOMOTIVE* INDUSTRIAL* MICRO-ELECTRONICSmilspecwest.comsales@milspecwest.com949-636-9677